



Booking #: 664302

Booking Name: Wells Fargo Base 26MY

Booking Revision #: 3

Dealer/Customer: WELLS FARGO EQUIPMENT (ST LOUIS,MO)TRL

Contact: WELLS FARGO EQUIPMENT FINANCE INC

Sales Person: Jeffrey Thompson

Expiration Date: 1/6/2025

Date: 11/7/2024

Requested Date: 03/01/2025

Dealer/Branch P.O:

Customer #: 190770

Customer P.O:

Itm	Product	Reference #	Name	Model #	Qty
1	CCC - Champion Composite Plate	C-195362	Wells Fargo Base 26MY	CCC-3314-01053	300

Line Item 1

Configuration Reference #: C-195362

Configuration Name: Wells Fargo Base 26MY

FG Item: 26218xxxx

Product: CCC - Champion Composite Plate

Model #: CCC-3314-01053

Mode of Transportation: Customer Pick-Up

Product

Product CCC - Champion Composite Plate

Manufacturing Plant Terre Haute, IN

Model Year 2026

Geometric Dimensions

CARB/CA Phase 2 GHG CARB/GHG2 compliance not required.

Packaged Options None

Serial Identification U.S. Certification

Overall Height 13' 6"

Overall Length 53' 0"

Overall Width 102.36"

Upper Coupler Height 47"

Kingpin Location 36.00"

Landing Gear Location 98.5" From Kingpin

Wedge 1.00" Wedge

Undercarriage Design Tandem Axle, Slide Air-Ride Suspension, 49" Axle Centers

Miscellaneous Text (TAB A) None

Front



Front Corner Type	4.7" Extruded Aluminum Radius
Front Corner Sheet	0.125" Extruded Aluminum Mill Finish
Front Corner Protectors	None
Front Sheets	Aluminum, 0.050"
Front Upright	Four (4) 18ga STL, 2.5" Hats
Front Vents	None
Quantity and Type of Front Vent	None
Location of Front Vent	None
Electrical Connector and Gladhand Location	Offset Roadside, Overlaid
Hose Couplers (Gladhands)	Great Dane Control and Supply with Urethane Seals
In-Line Air Filter	None
Document Holder	Great Dane Standard with Logo At Roadside Front
Additional Manifest Box	None
Additional Manifest Box Location	None
Miscellaneous Text (TABB)	None
Telematics	
Telematics / Tracking System	FleetPulseGo Track
Alternative Telematics System	...
Telematics System Install and Commission	Factory Furnished and Factory Commissioned
Telematics System Installation Detail	Great Dane Standard Location
Telematics / Tracking Power Supply	...
Side Exterior and Structural	
Side Sheet Material	Composite Plate, 0.30" with .016" PP Galv. Steel Skins
Side Sheet Texture	Flat
Side Post Type	Logistic Post, Comp Plate Single-Punch "A" (14 Gauge)
Side Post Spacing	50" Centers
Bottom Rail Fasteners	0.38" Aluminum Rivets
Rub Rail Type	None
Rub Rail Location	None
Side Skylight Quantity	None
Side Skylight Location	None
External Protection Package (Lift Pads)	None
Miscellaneous Text (TABC)	None
Rear	
Rear Frame Type	EnduroGuard Swing Door Frame
Header Type	2.5" Narrow Header
Rear Corner Post Lamp Protection	None
Rear Liftgate	None
Rear Bumpers	Rubber Dock Bumper
Rear Impact Guard	Hot Dip Galvanized Steel Rear Impact Guard Bolt on Vertical Weld On Horizontal
Dock Lock Bracing	None
Rear Access System	None



Tag Bracket Location	Standard Location
License Plate Installation	Customer Furnished License Plate to be Installed
Miscellaneous Text (TABE)	None
Rear Doors	
Rear Door Type	0.50" Composite Swing Door, Dual-Seal Gaskets, Galvanized Steel Cover Sheet
Lockrod	1 Per Door
Hinge per Door	4 Per Rear Door
Rear Door Holdback	K-Slot Style w/chain
Rear Door Vent	None
Rear Vent Location	None
Hazardous Placard	None
Haz. Mat. Placard Location	None
Miscellaneous Text (TABF)	None
Roof Options	
Roof Bows	1" Galvanized Steel, 24" Centers
Roof Sheet	Aluminum
Miscellaneous Text (TABG)	None
Floor	
Special Floor Rating	None
Type of Floor	Hardwood, Lam. 1.38"
Hardwood Floor Top Finish	Water Repellant Coating Rear 8'
Hardwood Floor Undercoat	PUR Polyurethane Front 5' Rear 15' (Two Outer boards Only)
Floor Brand	ProLam
Quantity of Wood Floor Screws	3 Screws per Board
Threshold Plate	HDGV Steel Diamondette, 0.125" x 24"
Miscellaneous Text (TABH)	None
Lining / Scuffband	
Front Lining	Pine Plywood, 0.50"X48" High, 0.25" to Ceiling
Ceiling Lining	None
Unit Numbers on Lining	Unit Numbers on Lining @ Top Rear Curbside
Rows of Front Scuffband	1 Row
Rows of Side Scuffband	2 Rows
Sidewall Cargo Restraint	None
Quantity of Rows of Logistic track	None
Miscellaneous Text (TABI)	None
Scuff/Logistic Track	
Type of Front Scuffband	12" Carbon Steel Welded to Coupler, 7 Gauge
Front Scuffband Location	Installed at Floor Level
Front Scuffband Position	Overlaid
Type of Side Scuffband (Row One)	5" Extruded Aluminum Integrated With Bottom Rail
Scuffband Location (Row One)	Installed at Floor Level
Type of Side Scuffband (Row Two)	6" Galvanized Steel, 18 gauge Roll Formed
Side Scuffband Location (Row Two)	Butted to lower row



Miscellaneous Text (TABJ)	None
Understructure	
Upper Coupler Type	3.50" Channel
Bottom Plate Thickness	0.25" with Rolled-Lip
Landing Gear	GD60
Landing Gear Foot / Shoe Type	10" X 10" Cushion Foot
Landing Gear Handle Location	Roadside
Landing Gear Lube System	No Special Lube System
Anti-Hook Plate	None
Tire Carrier	None
Crossmembers Ahead of Landing Gear	Steel Hat type on 12" Centers, 2" Deep
Crossmembers Over Landing Gear	4" Steel I-Beam on 12" Centers
Bay Area Crossmembers	4" Steel I-Beam on 12" Centers
URG Crossmembers	4" Steel I-Beam on 12" Centers
Extra Crossmembers at Rear	None
Extra URG Rail Length	None
Miscellaneous Text (TBHH)	None
Aerodynamic Devices	
Aerodynamic Fairings - Front, Gap Reducers	None
Front Fairing Color	None
Aerodynamic Fairings - Skirts, Undercarriage	None
Side Fairing Color	None
Aerodynamic Fairings - Tails, Rear Frame Fairings	None
Rear Fairing Color	None
Miscellaneous Text (TABK)	None
Suspension	
Model of Suspension	Hendrickson ULTRAAK 40K
Axle Type	Hendrickson Tapered Spindle Standard Wall
Integrated Wheel End Package	None
Locking Mechanism	Air-Assist Pin Release
Dump Valve	Surelok Feature
Miscellaneous Text (TABL)	None
Rear Ramps and Mud Flaps	
Mudflaps	Great Dane, Black with Logo
Mudflap Quantity/Bracket Material	1-Pair
Mudflap Mounting Location	On Undercarriage
Miscellaneous Text (TABM)	None
Brakes, Tire Inflation Systems and Wheel Ends	
Brake Size	16.50" x 7.00"
Brake Actuators	Great Dane Standard 2.5" Stroke
Brake Lining	Standard Brake Lining



Brake Shoe Type	Extended Service
Brake Adjusters	Meritor Automatic 5.50"
Supplemental Brake Stroke Indicator	None
Dust Shield Type	None
Tire-Inflation-System/Tire/Wheel Options	Hendrickson TIREMAAX PRO
Tire Inflation System Pressure	Great Dane Standard Pressure Setting
Auxiliary Pressure Check Port	None
Wheel Seals	Stemco Guardian
Axle Spindle Nuts	Auto-Torq Spindle Nut
Hubcaps	Hubcap To Accommodate Tire Inflation System
Wheel Lubricant	Kendall EBL Grease
Anti-Lock Brakes	Wabco 2S/1M Easy Stop
ECU Monitored Option	None
Brake Valves	Great Dane Standard Spring Brake Priority
Air-Tank Drain Valve	Manual
Hubodometer YN	None
Miscellaneous Text (TABN)	None
Tires / Wheels / Hubs and Drums	
Rim/Disc Wheel Size	22.5" X 8.25"
Hub/Wheel And Drum	Great Dane Hub Piloted Universal 10 Stud Hub with Outboard Cast Drums
Brake Drum Balancing	Supplied Balanced Only
Wheel Type	22.5" Steel Disc Wheel, Hub Piloted, 5HH
Wheel/Rim Vendor	Great Dane
Wheel Stud Options	Standard
Wheel Spacer (Corrosion Barrier)	None
Tire Size	295/75R 22.5
Tire Brand	Bridgestone Ecopia R123 (G)
Spare Tire	None
Miscellaneous Text (TABO)	None
Electrical	
Exterior Light Package	All Lights LED, Grote Long Life Light System, AMP Connector, Grote MicroNova Dot Lamps
Electrical Connector Type	Great Dane Standard 7-Way Solid Pin
Front Top Rail Lights Loc	1 Top Mounted on Front Corner at 45 Degrees; Roadside and Curbside (Canadian Requirement)
Buckplate Light Type	Grote Series 40, LED Flange Mount
Buckplate Lights Qty & Loc	2 Each Side
Stainless Theft-Resistant Flange for LED Lamps	Installed on Buckplate lamps with Stainless Rivets
Rear Header Light Locations	Center Cluster of 3 with Dual Intensity Brake Indication
Top and Bottom Side Marker Lamps/Location	Standard Lamp Package, 1 Each Side Top Rail @ Front, 1 Each Side Mid-ship Combination (req'd on trlrs 30' and over), 1 Each Side Bottom Rail @ Rear
Midship Turn Signal	Grote LED Combination Turn and Clearance
Location of Turn Signal	Roadside and Curbside, Center of Trailer



Installation of Turn Signal	Install Below Bottom rail
Supplemental Turn Signal	None
Type of Supplemental Turn-Signal	None
Location of Supplemental Turn Signal	None
Installation of Supplemental turn Signal	None
Miscellaneous Text (TABP)	None
Electrical Interior	
Interior Light Quantity	None
Interior Light Vendor/Type	None
Interior Light Location Width-wise	None
Interior Light Location Length-wise	None
Interior Light Switch Qty / Type / Loc	None
Miscellaneous Text (TABQ)	None
Finish/Paint/Decal	
Front Finish	Pre-Painted White
Side Finish	Pre-Painted White
Rear Frame Finish	Great Dane White
Rear Door Finish	Pre-Painted White
Undercarriage / Frame Finish	Black Undercoat
Wheel Finish	White Powder Coat
Upper Coupler Finish	Great Dane Standard Coating
Landing Gear Finish	Hot Dip Galvanized Wingplates Fore/Aft Bracing K Brace and Cross Shaft, Leg Finish to Match Undercarriage
Upper Running Gear Finish	Great Dane Standard Coating
Conspicuity Treatment Location	Great Dane on Side Sheet
Manufacturer's Logo Installation	Red Logos
Installation Of Customer Decals	INSTALL CUSTOMER FURNISHED DECAL ON NOSE (EMERGENCY NUMBER).
Exterior Unit Numbers	GREAT DANE TO FURNISH & INSTALL TWO SIX DIGIT HORIZONTAL UNIT NUMBERS, 4" DIGITS. One on front and one on rear.
Miscellaneous Text (TABR)	None
Calculated Values	
Production Line	Dry Production Line 1
Coupler PN	10200271-000001 3.50, 0.25 Btm Plt, 36KP, Painted
CARB Compliance Year	2025
Insulation	
Floor Insulation	None
Geometric Dimensions	
Drop Depth	None
Calculated Values	
Side Door Y/N	No
Rear Liftgate	
Liftgate Preparation	None
Lining / Scuffband	



Side Lining No Side Lining

Suspension

Pintle Hook None

Rear Ramps and Mud Flaps

Walkramp at Rear None

Exterior Unit Numbers - GREAT DANE TO FURNISH & INSTALL TWO SIX DIGIT HORIZONTAL UNIT NUMBERS, 4" DIGITS. One on front and one on rear.

EENID-1 BOMID-682277 CPQ-

Installation Of Customer Decals - INSTALL CUSTOMER FURNISHED DECAL ON NOSE (EMERGENCY NUMBER).

EENID-2 BOMID-CFM00073221 CPQ-